

SPECIFICATION SHEET: WH6-120-L

This Is An Original Product From Fulham Co., Inc

Description: WorkHorse Series Versatile, Solid State Electronic Ballast. Small Case Size,


High Power Factor, Light Weight, Available In 120/230/277V 50/60 Hz.


This Ballast Will Operate Following Lamps.

REFER TO LAMP WATTS/TYPE

ELECTRICAL DATA

INPUT VOLT: 120V ± 10%, 50/60Hz										
LAMP WATTS/TYPE	F21T5	F28T5	F21T5	F28T5	F14T5	F14T5	CFT40W	CFQ13W		
LAMPS OPERATED	3		4			3	2	3		
INPUT WATTS	63	79	74	95	59	48	85	45		
LINE CURRENT:	0.56	0.69	0.66	0.83	0.52	0.43	0.76	0.40		
POWER FACTOR	0.94	0.95	0.94	0.95	0.93	0.93	0.94	0.93		
BALLAST FACTOR	0.88	0.85	0.79	0.76	0.90	1.01	0.95	1.01		
EFFICACY FACTOR	1.40	1.08	1.06	0.80	1.53	2.11	1.12	2.26		
THD	34.4%	32.2%	33.5%	30.8%	35.6%	37.1%	33.1%	37.3%		
EMI/RFI COMPLIANCE		FCC PART 18-A(non-Consumer)								
SOUND RATING		"A"								
BALLAST TYPE	INSTANT START									
VOLTAGE TRANSIENTS	ANSI 62.41									
INPUT/PROTECTION	FUSE									
MINI. LAMP START	SEE LAMP SPECS									
MIN. BALLAST OPERATING TEMP	-30 °C (-20 °F)									
MAX. CASE TEMP	70 °C (158 °F)									
APPROVALS/CLASS	UL LISTED, CLASS " P ", 1 OR 2 OUTDOOR									





Fulham Co., Inc extends limited warranty only to the original purchaser or to the first user for the period of 5 years from the date of manufacture as indicated by the date code stamped on each product and when properly installed and under normal conditions of use. For additional warranty guide line, please refer to our Complete Product Catalog OR <u>call Customer Service at 1-323-599-5000</u>.

DUE TO A PROGRAM OF CONTINUOUS IMPROVEMENT, FULHAM Co., INC RESERVES THE RIGHT TO MAKE ANY VARIATION IN DESIGN OR CONSTRUCTION TO THE EQUIPMENT DESCRIBED.



SPECIFICATION SHEET: WH6-120-L

This Is An Original Product From Fulham Co., Inc

Description: WorkHorse Series Versatile, Solid State Electronic Ballast. Small Case Size,


High Power Factor, Light Weight, Available In 120/230/277V 50/60 Hz.


This Ballast Will Operate Following Lamps.

REFER TO LAMP WATTS/TYPE

ELECTRICAL DATA

INPUT VOLT: 120V ± 10%, 50/60Hz								•	
LAMP WATTS/TYPE	* F40T8	* F58T8	F54T5HO	CFQ13W					
LAMPS OPERATED	2	. 1	1	4					
INPUT WATTS	67	47	61	54					
LINE CURRENT:	0.59	0.43	0.55	0.48					
POWER FACTOR	0.94	0.93	0.93	0.93					
BALLAST FACTOR	0.86	0.83	1.06	0.98					
EFFICACY FACTOR	1.28	1.75	1.73	1.80					
THD	34.8%	37.5%	36.2%	36.1%					
EMI/RFI COMPLIANCE	FCC PART 18-A(non-Consumer)								
SOUND RATING	" A "								
BALLAST TYPE	INSTANT START								
VOLTAGE TRANSIENTS	ANSI 62.41								
INPUT/PROTECTION	FUSE								
MINI. LAMP START	SEE LAMP SPECS								
MIN. BALLAST OPERATING TEMP	-30 °C (-20 °F)								
MAX. CASE TEMP	70 °C (158 °F)								
APPROVALS/CLASS	UL LISTED, CLASS " P ", 1 OR 2 OUTDOOR								





Fulham Co., Inc extends limited warranty only to the original purchaser or to the first user for the period of 5 years from the date of manufacture as indicated by the date code stamped on each product and when properly installed and under normal conditions of use. For additional warranty guide line, please refer to our Complete Product Catalog OR <u>call Customer Service at 1-323-599-5000</u>.

DUE TO A PROGRAM OF CONTINUOUS IMPROVEMENT, FULHAM Co., INC RESERVES THE RIGHT TO MAKE ANY VARIATION IN DESIGN OR CONSTRUCTION TO THE EQUIPMENT DESCRIBED.