



KT-PLED40-22-8XX-VDIM

LED PANEL LIGHT

DESCRIPTION

2'x2' LED panel light, 40W family, 120-277V input, 0-10V dimming





PRODUCT FEATURES

- Low profile architectural grade design
- Fits standard T-grid ceilings
- Suitable for surface or suspension mount with optional accessories
- High quality laser etched PMMA resin light guide plate offers optimal light diffusion with no risk of yellowing over product lifetime
- Powered by Keystone 0-10V dimming LED driver with built-in junction box
- Compatible with Keystone SmartSafe emergency LED drivers; KT-EMRG-LED-5-500-EN /DF or KT-EMRG-LED-12-1200-EN /DF are optimal for fixture level installation; mounting kit KT-PLED-EM-BR-KIT required (sold separately)
- 60,000 hour rated life
- Over 50% energy savings as compared to traditional fluorescent troffers
- LED color binning within 4 SDCM ensures supreme color consistency between all panels
- Operating temperature range: -20°C/-4°F to 40°C/104°F
- Suitable for damp locations

PERFORMANCE SPECIFICATIONS

| Catalog Number | Input Voltage | Wattage | Color Temperature | Lumen Output | CRI | Power Factor | Efficacy | Lifetime |
|-----------------------|---------------|---------|-------------------|--------------|-------|--------------|----------|--------------|
| KT-PLED40-22-835-VDIM | 120-277V | 40W | 3500K | 4,050 | >81.4 | >0.9 | 101 lm/W | 60,000 Hours |
| KT-PLED40-22-840-VDIM | 120-277V | 40W | 4000K | 4,100 | >81.4 | >0.9 | 103 lm/W | 60,000 Hours |
| KT-PLED40-22-850-VDIM | 120-277V | 40W | 5000K | 4,150 | >81.4 | >0.9 | 104 lm/W | 60,000 Hours |

PHOTOMETRIC SPECIFICATIONS




| Zonal Lumen Summary | | |
|---------------------|---------|-------------|
| Zone | Lumens | % Luminaire |
| 0-30 | 1,117.2 | 27.9% |
| 0-40 | 1,818.1 | 45.3% |
| 0-60 | 3,174.6 | 79.2% |
| 60-90 | 835.3 | 20.8% |
| 70-100 | 351.4 | 8.8% |
| 90-120 | 0.0 | 0% |
| 0-90 | 4,009.9 | 100% |
| 90-180 | 0.9 | 0% |
| 0-180 | 4,010.8 | 100% |



KT-PLED40-22-8XX-VDIM

LED PANEL LIGHT

PHYSICAL SPECIFICATIONS



WEIGHT INFORMATION

| 1 Piece | 1 Carton |
|----------|-----------|
| 7.50 lbs | 17.81 lbs |

ACCESSORIES (SOLD SEPARATELY)

| Accessory | Catalog Number | Description |
|------------------------------------|----------------------------|--|
| Cable Hanging Kit | KT-PLED-CABLE-KIT | Cable hanging kit for LED panel lights (includes 3 cable sets) |
| Surface Mount Kit | KT-PLED-SM-22-KIT | Surface mount kit for (1) 2x2 LED panel light |
| SmartSafe Emergency Battery Backup | KT-EMRG-LED-5-500-EN /DF | 5W, 500 lumen SmartSafe emergency battery back-up with dual flex cables |
| | KT-EMRG-LED-12-1200-EN /DF | 12W, 1200 lumen SmartSafe emergency battery back-up with dual flex cables for remote mounting only |
| Emergency LED Backup Mounting Kit | KT-PLED-EM-BR-KIT | Bracket kit for mounting emergency LED backup to LED panel lights; designed for use with KT-EMRG-LED-5-500-EN /DF and KT-EMRG-LED-12-1200-EN /DF |

CATALOG NUMBER BREAKDOWN

KT-PLED40-22-8XX-VDIM

1 2 3 4 5 6 7

- 1 Keystone Technologies
- 2 Panel Light LED Fixture
- 3 Wattage
- 4 2' x 2' Nominal Size
- 5 800 Series
- 6 Color Temperature
- 7 0-10V Dimming