



Switch Start Metal Halide Protected

MH 150W/640 E26 CL 1SL/24

An efficient, protected "O" rated lighting solution that is suitable for open-rated fixtures. Ideal for both indoor and outdoor applications.

Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

Product data


General Information		Chromaticity Coordinate Y (Nom)	
Cap-Base	E26 [Single Contact Medium Screw]	Correlated Color Temperature (Nom)	4000 K
Operating Position	H [Hanging or Base Up (BU)]	Luminous Efficacy (rated) (Nom)	87 lm/W
Life to 5% Failures (Nom)	2000 h	Color Rendering Index (Nom)	65
Life to 50% Failures (Nom)	15000 h	Operating and Electrical	
System Description	-	Power (Rated) (Max)	- W
Light Technical		Power (Rated) (Min)	- W
Color Code	640 [CCT of 4000K]	Power (Nom)	155 W
Luminous Flux (Rated) (Min)	12150 lm	Lamp Current Run-Up (Max)	3 A
Luminous Flux (Rated) (Nom)	13500 lm	Lamp Current (EM) (Nom)	1.8 A
Color Designation	Cool White (CW)	Ignition Supply Voltage (Max)	198 V
Lumen Maintenance 10000 h (Nom)	58 %	Ignition Supply Voltage (Min)	198 V
Lumen Maintenance 2000 h (Nom)	73 %	Voltage (Max)	105 V
Lumen Maintenance 5000 h (Nom)	64 %	Voltage (Min)	85 V
Chromaticity Coordinate X (Nom)	385		

Switch Start Metal Halide Protected

Voltage (Nom)	95 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Approval and Application	
Mercury (Hg) Content (Nom)	11 mg
Energy Consumption kWh/1000 h	165 kWh
Luminaire Design Requirements	
Bulb Temperature (Max)	450 °C

Cap-Base Temperature (Max)	250 °C
Product Data	
Order product name	MH 150W/640 E26 CL 1SL/24
EAN/UPC - Product	046677137526
Order code	928486000191
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	928486000191
Net Weight (Piece)	0.074 kg

Dimensional drawing



MH 150W E26 ED17 CL

Product	D (max)	L (min)	C (max)
MH 150W/640 E26 CL 1SL/24	56 mm	83 mm	138 mm

