

Project Name

Location

Prepared By



SATCO S18413

15T8/U6/LED/5CCT/DUAL

Notes

(www) 05-07-2023 00:43:13

General

| | |
|-------------------------|-------------------------------|
| Status | Active |
| Watts | 11.5W/13W/15W |
| Incandescent Equivalent | 50W |
| Fluorescent Equivalent | 32W |
| Volts | 120V-277V |
| Ballast Type | Type A/B |
| Shape | T8 |
| Base | Medium Bi Pin |
| ANSI Base | G13 |
| Finish | Frost |
| CCT (Kelvin) | 3000K/3500K/4000K/5000K/6500K |
| Temperature | Soft White to Daylight |
| CRI | 80+ |
| Lumens | 1800L/2000L/2200L |
| Beam Spread | 210 |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Product Category | U-Bend |
| Technology | LED |

Electrical

| | |
|-------------------------|---|
| Ballasting Requirements | Ballast required (Type A) or Ballast Bypass (Type B) |
| Operating Frequency | 50/60Hz |
| Dimming Note | Only in Type A mode; Check Ballast MFG for Dimmer Compatibility |
| Power Factor | >0.9 |
| THD | <20% |
| Operating Temperature | -20C (-4F) to +45C (+113F) |

Physical

| | |
|---------------|-------|
| MOL | 22.43 |
| MOD | 0.96 |
| Leg Spacing | 5.98 |
| Material | Glass |
| Lens Finish | Frost |
| Lens Material | Glass |
| Housing Color | White |
| Weight (lb.) | 0.55 |

Additional Information

| | |
|----------------------------|---|
| Installation Notes | Not for use in vapor tight fixtures. Direct replacement for 32W T8 U6 lamps only. |
| Rated For Enclosed Fixture | Yes |
| Warranty | 5 Years |

Compliance

| | |
|----------------------|---|
| Safety Listing | cULus - Certified; cULus - Classified; cULus - Listed |
| Location Rating | Damp |
| DLC Approved | Yes |
| DLC ID | S-GDKRYT |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| NSF Approved | Yes |
| SDS Sheet | LED_Lamp |